_					
M	AGNAFLUX	®			
	Division of Illinois Tool Works Inc				
Date:					
Purch	ase Order No:				
Subje	ct:	Туре:			
Batch	No				
		t time of manufacture, the abound has been tested for sulfur ar		0:	
	including 2005, 200 B. ASME Boiler and Pr Examination, includi C. ASME Boiler and Pr	ressure Vessel Code, 1986, 19 6 including 1992 Addenda,Pa	Article 6 Paragraph T-640 98, & 2001 Edition, Sect denda, Article 6 Paragra 989 and 1992 Edition, S	0 and Article 24 as applicable. tion V Nondestructive uph T-640 and Article 24 as applicable. Section V, Nondestructive	
	D. ASTM E-165-92, ASTM E-165-94, ASTM E-165-95, ASTM E-165-02, and ASTM E-165-09 Paragraph 7.1.				
	E. MIL-STD-271F(SH), 27 June 1986, Paragraphs 5.3 and 5.3.1., including Notice 1 Paragraph 5.6.1 (21, June 1993).				
	F. NAVSEA T9074-AS	-GIB-010/271, 30 April 1997, P	aragraph 5.3.1 & 5.6.2, i	including Notice 1.	
	G. MIL-STD-2132D, 11 F	ebruary 2003, Paragraph 7.1, 7.1.	2., 7.1.3, Appendix C, Para	agraph 40	
The foll	owing test results were obtain	ed:			
	Sulfur:	wt, % of residue. CL+F:	w	t, % of residue	
	Cleaner residue (see note 3)	<u>c</u>	y/100g	g/100ml	
2.	We further certify that this ma	aterial does not contain mercur	y as a basic element an	d no mercury bearing equip-	
	ment was used in its manufa	cture.			
	MAGNAFLUX® Mathew Planoty				
			Plamoottil - Quality A	Assurance Mgr.	
		L.	pola Carle		
			arle - Lab Technician).	
Notes:	 Our batch number appears on the bottom of all aerosol cans and on the label of all bulk containers. Most specifications require test results stated in percent but some require parts per million (ppm). To convert "percent" figures to "parts per million" move the decimal four places to the right. The above certification gives the results obtained at the time of manufacture. Age and use may alter the properties of any material 				
				Form No. F-1568 R-9/09	
3624	WEST LAKE AVENUE 🔳 G	LENVIEW, ILLINOIS 60025	TEL (847) 657-530)0 🔳 FAX (847) 657-5388	



Date:	
Purchase Order No.	
We hereby certify that the, Batch No, supplied meets the requirements approved by the U.S. Air Force.	of AMS 2644E, and is
When tested according to paragraph 4.3.2., Sampling Plan A, the followin	g results were obtained.
4.2.2.1. Penetrant Tests: Flash Point (PMCC), 3.3.3 Viscosity, 3.3.4(cs. Nominal) Fluorescent Brightness, 3.3.8.3.2.(FP-4PE Standard) Water Tolerance (Method A only), 3.3.8.5 Removability, 3.3.8.6	°F cs@100°F
4.2.2.1 Emulsifier Tests:	
Flash Point (PMCC), 3.3.3 Viscosity, 3.3.4(cs. Nominal) Water Content (Method D only), 3.3.9.6	<u> </u>
4.2.2.3. Developer Tests:	
Developer Fluorescence, 3.3.10.2 Developer Removability, 3.3.10.4 Redispersibility, 3.3.10.5	
3.3.11.5 Remover Tests:	
Penetrant Removal, 4.4.11.3.2	<u>.</u>

We further certify that this material meets the requirements of ASTM E 1417, Paragraph 5.1.

MAGNAFLUX®

Mathew Planooth

Mathew Plamoottil - Quality Assurance Mgr.

Lynda Carle Lynda Carle - Lab Technician.

Form No. F-1579E R-12/06

3624 WEST LAKE AVENUE 🔳 GLENVIEW, ILLINOIS 60025 🔳 TEL (847) 657-5300 🔳 FAX (847) 657-5388