

# EV6000

## Hand-Held LED UV Lamp

The EV6000 LED UV lamp is a portable, hand-held UV lamp for fluorescent non-destructive testing applications like fluorescent penetrant testing and fluorescent magnetic particle inspections.

The EV6000 features a large 9 in / 23 cm, uniform beam without hot spots that is one of the widest in the industry.

Custom-designed optics provide intense, even coverage of UV-A to easily identify indications, and an integrated filter ensures minimal visible light emission to improve inspection reliability.

The EV6000 is certified to NDT standards for LED UV lamps and certified for Aerospace Prime and OEM specifications for emission spectrum and beam profile. Each unit is shipped with a manufacturer's certificate of conformance which meets or exceeds all current specifications for use with fluorescent liquid penetrant and magnetic particle testing.



### BENEFITS

#### Minimizes time to inspect parts

- Speeds up inspection time with one of the widest, most even beams on the market
- Indications are clearly visible even at the edge of the 9 inch / 23 cm beam, thanks to the high intensity LEDs

#### Maximize range of inspections

- Use for virtually any fluorescent penetrant or mag particle inspection
- Inspect a wide range of components, including aerospace parts, without worry
- Full NDT specification compliance, including ASTM E3022, RRES 90061, and AITM6-1001

#### Increases real-world reliability

- Reduces on-the-job downtime with dependable, reinforced construction
- Fully sealed IP65 rated housing will stand up to the elements

### FEATURES

- 9 in / 23 cm wide, uniform beam
- No hot-spots in the beam profile
- IP65 rated, rugged, durable design
- No internal fan
- Low energy consumption
- Aerospace prime and OEM certified
- Certified to ASTM / RRES / AITM

### SPECIFICATION COMPLIANCE

- ASTM E2297
- ASTM E3022
- ISO 3059
- RRES 90061

**Penetrant Testing Specifications:**

- Airbus AITM6-1001
- ASME BPVC
- ASTM E165
- ASTM E1417
- ASTM F601
- ISO 3452
- NADCAP AC7114/1

**Magnetic Particle Testing Specifications:**

- ASME BPVC
- ASTM E709
- ASTM E1444
- ASTM E3024
- ISO 9934
- NADCAP AC7114/2

**PRODUCT PROPERTIES**

<b>Max. Irradiance*</b>	5,000 $\mu\text{W}/\text{cm}^2$
<b>Peak Wavelength</b>	365 $\pm$ 5 nm
<b>Typical Beam Profile*</b>	Circular spot, 9 in / 23 cm diameter, > 1,000 $\mu\text{W}/\text{cm}^2$ UV-A intensity
<b>Excitation Irradiance</b> (347-382 nm)	$\geq$ 2,000 $\mu\text{W}/\text{cm}^2$
<b>Working Distances</b> ASTM RRES 90061	Min. WD $\leq$ 6 in / 13 cm Min. WD = 15 in / 38 cm Max. WD = 36 in / 92 cm
<b>Typical Visible Emission</b> ASTM RRES 90061 range (390-800 nm)	$\leq$ 2 ft-candles* $\leq$ 20 lux at 15 in / 38 cm $\leq$ 5 lux at 36 in / 92 cm
<b>Stabilization Time</b>	5 minutes at ambient conditions
<b>Lamp Cord Length</b>	17 ft / 5.18 m
<b>Power Supply Cord Length</b>	9 ft / 2.75 m
<b>Weight</b>	2 lb / 0.9 kg
<b>Power In</b>	100-240 VAC / 50-60 Hz / <1A

\* At 15 in / 38 cm

**USE RECOMMENDATIONS**

<b>NDT Method</b>	Fluorescent Penetrant Testing and Mag Particle Inspection
<b>Recommended Accessories</b>	UV-A Meter, PN 625024 Visible Light Meter, PN 622338 UV-A Safety Glasses, PN 506249

**PART NUMBERS**

EV6000	625784
EV6000 ZP Kit	626776
EV6000 MG Kit	626779
EV6000 CSA	628785